

## ELECTRIC TELESCOPIC BOOM LIFTS

# TB32EJN PLUS (TB1060EJN PLUS)

Compliant with CE/ANSI/EAC standards

## PRODUCT HIGHLIGHTS

### Fixed Axle

- Narrow series of 32.3m(106') with fixed axle of 2.49m(8'2") width

### Green

- Comfortable working environment without noise pollution, meet indoor or emissions-critical site requirements

### Precision Performance

- 3 joysticks with variable proportional control, operate with smooth starting and stopping and precision approach to your worksite target
- The telematics and intelligent 7-inch screen can efficiently control the use and behavior of the equipment

### Economical

- Battery quality assurance, low failure rate and reduced maintenance costs compared with diesel power, which reduces overall operating cost

### Strong Site Passing Performance

- Both the active and inactive states have an oscillating function, allowing work to be performed on inclines and uneven ground



Standard Features		
Active oscillating function	7-in display screen	4WD x 2WS
Proportional control with 3 joysticks	Automotive-grade sleeves for all pipes	4-wheel brake
Hydraulic platform leveling	160° Platform rotation	Weighing system
Tilt protection system	Max tilt rating to 5°	Emergency stop system
Flashing beacon	Horn & buzzer	Emergency lowering system
Footswitch	2.44 m(8') platform	Fault diagnosis system
Foam-filled non-marking tires	Manual storage box	
Options & Accessories		
AC power to platform	Solid tires	1.45 m (4'9") platform
1.83 m(6') work platform	2.44 m(8') platform with swinging gate	Platform work light
Secondary guarding device	Overhead anti-collision device	Glazier kit(for platform with swinging gate)
Lithium battery	Telematics-ready connector	Half mesh (for platform with swinging gate)

**SINOBOOM™**

**PARTNERS IN ACCESS™**

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

ELECTRIC TELESCOPIC BOOM LIFTS

TB32EJN PLUS(TB1060EJN PLUS)

Compliant with CE/ANSI/EAC standards

Model	TB32EJN Plus (TB1060EJN Plus)
Dimensions	
Max Platform Height	32.3 m (106')
Max Working Height	34.3 m (112'6 ")
Max Horizontal Reach (Restricted/Unrestricted)	17.8 m/19.5 m (58'5" / 64')
A Stowed Length	12.76 m (41'10")
B Stowed Width	2.49 m (8'2")
C Stowed Height	2.88m (9'5")
Stowed Length (Transport)	9.73 m (31'11")
Stowed Width (Transport)	2.49 m (8'2")
Stowed Height (Transport)	2.88 m (9'5")
D Wheelbase	3 m (9'10")
Ground Clearance	0.46 m (1'6")
Platform Size (L×W×H)	2.44 m×0.91 m×1.1 m (8'×3'×3'7")
Performance	
Max Platform Capacity (Restricted/Unrestricted)	454 kg/300 kg (1,000 lbs/661 lbs)
Max Platform Occupants (Restricted/Unrestricted)	3 Persons/2 Persons
Drive Speed (Stowed)	0~6 km/h (0~3.7 mph)
Drive Speed (Raised)	0~1.1 km/h (0~0.68 mph)
Gradeability	45%
Turntable Rotation	360°/Continuous
Platform Rotation	160°
Tilt Rating	5°
Turning Radius (Inside/Outside)	3.65 m/6.91 m (11'11.7"/22'8")
Turntable Tail-Swing	1.45 m (4'9")
Max Allowable Side Force	400 N (90 lbf)
Max Allowable Wind Speed	12.5 m/s (28 mph)
Tire Spec/Type	385/65D22.5 (foam-filled)
Power	
Drive × Steer	4WDx2WS
Batteries	80 V, 480 Ah (lead acid battery) 80 V, 500 Ah (lithium battery)
Hydraulic Tank Capacity	180 L (39.6 gal (UK)/47.6 gal (US))
System Voltage	80 VDC
Weight	
Weight	18,370kg(40,498 lbs)
Standards Compliance	
CE/ANSI/EAC	

