

## ENGINE POWERED CRAWLER TELESCOPIC BOOM LIFTS

# TB22JT PLUS (TB730JT PLUS)

Compliant with CE /ANSI/EAC standards

### PRODUCT HIGHLIGHTS

- Industry-leading oscillating crawler chassis, adaptive to rough terrain, more comfortable and safer
- Spin turn makes it flexible in narrow places
- Industry-leading four-joystick proportional control for more movements, stable at high speed and precise at micro-movement
- Industry-leading load capacity of 454kg/340kg/250kg maximizes the performance of the machine, features large working range and high working efficiency



#### Standard Features

7-in display screen	Rubber plate	Dual-speed drive motor
Proportional control with 3 joysticks	Automotive-grade sleeves for all pipes	Weighing system
Hydraulic platform leveling	Continuous 360° turntable rotation	Emergency stop system
Tilt protection system	Max tilt rating to 5°	Emergency lowering system
Flashing beacon	Horn & buzzer	Fault diagnosis system
Footswitch	2.44m(8') platform	Foam-filled non-marking tires
Manual storage box	Anti-crush device	

#### Options & Accessories

AC power to platform	1.83m (6') platform	Overhead anti-collision device
Telematics-ready connector	Platform work light	

**SINOBOOM™**

**PARTNERS IN ACCESS™**

[SINOBOOM.COM](http://SINOBOOM.COM) | [SALES@SINOBOOM.COM](mailto:SALES@SINOBOOM.COM)

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

# ENGINE POWERED CRAWLER TELESCOPIC BOOM LIFTS TB22JT PLUS (TB730JT PLUS)

Compliant with CE /ANSI/EAC standards

Model	TB22JT Plus(TB730JT Plus)
<b>Dimensions</b>	
Max Platform Height	22.2 m (72'10")
Max Working Height	24.2 m (79'5")
Max Horizontal Reach(Restricted/ Restricted/Unrestricted)	14.5 m/15.8m/17m (47'7"/51'10"/55'9")
A Stowed Length	10.7 m (35'1")
B Stowed Width	2.49 m (8'2")
C Stowed Height	2.65 m (8'8")
Stowed Length (Transport)	8.8 m (28'10")
Stowed Width (Transport)	2.49 m (8'2")
Stowed Height (Transport)	2.77 m (9'1")
D Wheelbase	2.9 m (9'6")
Ground Clearance	0.4 m (1'4")
Platform Size (L×W×H)	2.44 m×0.91 m×1.1 m (8'×3'×3'7")
<b>Performance</b>	
Max Platform Capacity (Restricted/ Restricted/Unrestricted)	454 kg/340 kg/250 kg (1000 lbs/750 lbs/551 lbs)
Max Platform Occupants(Restricted/ Restricted/Unrestricted)	3 Persons/2 Persons/2 Persons
Drive Speed (Stowed)	0~1.8 km/h (0~1.1 mph)
Drive Speed (Raised)	0~0.5 km/h (0~0.3 mph)
Gradeability	40 %
Turntable Rotation	360° continuous
Platform Rotation	160°
Tilt Rating	5°
Turning Radius (Inside/Outside)	2.44 m (8')
Turntable Tail-Swing	1.44 m (4'9")
Max Allowable Side Force	400 N (90 lbf)
Max Allowable Wind Speed	12.5 m/s (28 mph)
<b>Power</b>	
Drive × Steer	2WD
Engine	43 kW/2500 rpm/ QSF2.8t3NA60/Cummins/China T3
Hydraulic Tank Capacity	180 L (39.6 gal(UK)/47.6 gal (US))
Diesel Tank Capacity	160 L (35.2 gal(UK)/42.3 gal (US))
System Voltage	12 VDC
<b>Weight</b>	
Weight	14,230 kg (31,371 lbs)
Standards Compliance	CE/ANSI/EAC

