

ENGINE POWERED TELESCOPIC BOOM LIFTS

TB32JN PLUS (TB1060JN PLUS)

Compliant with GB/CE/ANSI/EAC standards

PRODUCT HIGHLIGHTS

High Capacity

- Plus series boom lifts holds up to 1,000 lbs (restricted)/661 lbs (restricted)/551 lbs(unrestricted) platform capacity allowing you to carry up to 3 occupants plus material and tools to get your job done easily

Intelligent Maintenance

- Industry leading 7" screen displays faults and status information, for easy reference, reducing service technician assistance. Workers can complete tasks under the remote guidance of qualified service technicians. Convenient for fleet managers to quickly access live machine and maintenance information

Precision Performance

- The upper control box is equipped with 3 full-proportional handles for gradual control of boom lifting, telescoping, turntable rotation and driving speed. Operate with smooth starting and stopping and precision approach to your worksite target



Standard Features		
Active oscillating function	7-in display screen	4WD × 2WS
Proportional control with 3 joysticks	Automotive-grade sleeves for all pipes	Weighing system
Hydraulic platform leveling	160° Platform rotation	Emergency stop system
Tilt protection system	Max tilt rating to 5°	Emergency lowering system
Flashing beacon	Horn & buzzer	Fault diagnosis system
Footswitch	2.44 m(8') platform with swinging gate	Foam-filled non-marking tires
Manual storage box	Secondary guarding device	Overhead anti-collision device
Options & Accessories		
Foam-filled non-marking tires	Solid tires	Platform work light
Overhead anti-collision device	1.83 m(6') platform with swinging gate	Half mesh (For platform with swinging gate)
Glazier kit(For platform with swinging gate)	Anemometer	

SINOBOOM™

PARTNERS IN ACCESS™

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

ENGINE POWERED TELESCOPIC BOOM LIFTS

TB32JN PLUS (TB1060JN PLUS)

Compliant with GB/CE/ANSI/EAC standards

Model	TB32JN Plus (TB1060JN PLUS)
Dimensions	
Max Platform Height	32.3 m (105'12")
Max Working Height	34.3 m (112'6")
Max Horizontal Reach(Restricted/Restricted/Unrestricted)	17.9 m/20.0 m/20.9 m (58'9"/65'7"/68'7")
A Machine Length (Stowed/Transport)	12.76 m/9.73 m (41'10"/31'11")
B Machine Width (Stowed/Transport)	2.49 m/2.49 m (8'2"/8'2")
C Machine Height (Stowed/Transport)	2.88 m/2.88 m (9'5"/9'5")
D Wheelbase	3.0 m (9'10")
Ground Clearance	0.42 m (1'4.5")
Platform Size (L×W×H)	2.44 m×0.91 m×1.1 m (8'×3'×3'7")
Performance	
Max Platform Capacity (Restricted/Restricted/Unrestricted)	454 kg/300 kg/250 kg (1,000lbs/661lbs/551lbs)
Max Platform Occupants (Restricted/Restricted/Unrestricted)	3 persons/2 persons/2 persons
Drive Speed (Stowed/Raised)	0 ~ 4.8 km/h (0 ~ 3 mph) 0 ~ 1.1 km/h (0 ~ 0.68 mph)
Gradeability	45%
Turntable Rotation	360° /Continuous
Platform Rotation	160°
Tilt Rating	5°
Turning Radius (Inside/Outside)	3.65 m/6.91 m (12'/ 22'8")
Turntable Tail-Swing	1.45 m (4'8")
Max Allowable Side Force	400 N (90 lbf)
Max Allowable Wind Speed	12.5 m/s (28 mph)
Tire Spec/Type	385/65D22.5 (foam-filled) 385/65-24/10 (solid) 15-625 (foam-filled)
Power	
Drive × Steer	4WD × 2WS
Engine	54 kW/2400 rpm/ QSF2.8t3TC72/Cummins/China T3、 EU stage III 55.4 kW /2600 rpm/ TD2.9 L4/Deutz/EU stage V、 EPA Tier 4F 36.8 kW/ 2200 rpm/ YCF3050-T420-3040G1/Yuchai/China T4 36.5 kW / 2400 rpm/ YCF3050-T307-30D6G2 / Yuchai/China T3
Hydraulic Tank Capacity	180 L (39.6gal(UK)/47.6gal(US))
Diesel Tank Capacity	150L(33.0 gal(UK)/39.6 gal(US))
System Voltage	12 VDC
Weight	
Weight	17,460 kg (38,493lbs)
Standards Compliance	GB / CE / ANSI / EAC

