

ENGINE POWERED TELESCOPIC BOOM LIFTS

TB58RJ PLUS(TB1900RJ PLUS)

Compliant with CE/EAC standards

PRODUCT HIGHLIGHTS

Precision Performance

- Platform control unit equips 3 joysticks featuring proportional control, which is easy to operate and reach the work targets

Intelligent Maintenance

- Industry leading 7" screen displays faults and status information, for easy reference, reducing service technician assistance. Workers can complete tasks under the remote guidance of qualified service technicians. Convenient for fleet managers to quickly access live machine and maintenance information

Safe and Reliable

- Machine equips safety Rexroth controller with dual backup CPU and compliant with ISO 13849, high performance level d, combined with dual channel sensors offering an extremely safe redundancy



Standard Features

Proportional control with 3 joysticks	7-in display screen	4WD x 4WS
Electrical platform leveling	Automotive-grade sleeves for all pipes	Weighing system
Tilt protection system	160° platform rotation	Emergency stop system
Flashing beacon	170° jib rotation	Emergency lowering system
Footswitch	Horn & buzzer	Fault diagnosis system
Manual storage box	2.44 m(8') platform with swinging gate	Foam-filled tires
Max tilt rating to 5°	Telematics-ready connector	Secondary guarding device
Oil cooler		

Options & Accessories

AC power to platform	Platform work light	Overhead anti-collision device
Half mesh (For platform with swinging gate)	Glazier kit(For platform with swinging gate)	Anemometer

SINOBOOM™

PARTNERS IN ACCESS™

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

ENGINE POWERED TELESCOPIC BOOM LIFTS

TB58RJ PLUS(TB1900RJ PLUS)

Compliant with CE/EAC standards

Model	TB58RJ Plus (TB1900RJ Plus)
Dimensions	
Max Platform Height	57.9 m (189'11.5")
Max Working Height	59.9 m (196'6")
Max Horizontal Reach(Restricted/Unrestricted)	21.01 m/24.4 m (68'11"/80'1")
A Stowed Length	20.07 m (65'10")
B Overall Width (Axle Retracted / Extended)	2.49 m/5 m (8'2"/16'5")
C Stowed Height	3.1 m (10'2")
Stowed Length (Transport)	14.6 m (47'11")
Stowed Width (Transport)	2.49 m (8'2")
Stowed Height (Transport)	3.1 m (10'2")
D Wheelbase	5.2 m (17'1")
Ground Clearance	0.44 m (1'5.3")
Platform Size (L×W×H)	2.44 m×0.91 m×1.1 m (8'×3'×3'7")
Performance	
Max Platform Capacity(Restricted/Unrestricted)	454 kg/300 kg (1, 000 lbs/661 lbs)
Max Platform Occupants(Restricted/Unrestricted)	3 persons / 2 persons
Drive Speed (Stowed)	4.5 km/h (2.8 mph)
Drive Speed (Raised)	0.48 km/h (0.3 mph)
Gradeability	45 %
Turntable Rotation	360° / Non-continuous
Platform Rotation	160°
Jib Rotation	170°
Tilt Rating	5°
Turning Radius (Inside/Outside) (Outrigger retracted)	7.1 m/9.52 m (23'3.5"/31'3")
Turning Radius (Inside/Outside) (Outrigger extended)	2.28 m/6.54 m (7'5.8"/21'5.5")
Turntable Tail-Swing	2.32 m (7'7.3")
Max Allowable Side Force	400 N (90 lbf)
Max Allowable Wind Speed	12.5 m/s (28 mph)
Tire Spec/Type	445/50D710 24PR (Foam-filled)
Power	
Drive × Steer	4WD × 4WS
Engine	74 kW/ 2200 rpm/ YCF36100-T480/Yuchai/China T4 74 kW/ 2200 rpm/ QSF3.8t3TC99/Cummins/China T3 74.4 kW/2300rpm/TCD3.6 L4 Stage V+T4f/DETUZ/ EU Stage V ,T4f 74.4 kW/2300rpm/TCD3.6 L4 T4f/DETUZ/T4f
Hydraulic Tank Capacity	405 L (89.1 gal (UK)/107 gal (US))
Diesel Tank Capacity	200 L (44 gal (UK)/52.8 gal (US))
System Voltage	12 V DC
Weight	
Weight	27,600 kg (60,848 lbs)
Standards Compliance	CE/EAC

