

ENGINE POWERED TELESCOPIC BOOM LIFTS

TB42RJ (TB1370RJ)

Compliant with CE/EAC/AS standards

PRODUCT HIGHLIGHTS

Strong Site Passability Performance

- Machine features oscillating function, combined with power 4WD not only makes it perfect to work at uneven ground, but also greatly improves work efficiency

Precision Performance

- Proportional control with 3 joysticks, operate with smooth starting and stopping and precision approach to your worksite target
- 7-inch screen features one button's fault inquiries, easy for trouble shooting and calibration

High Capacity

- Leading load capacity of 480kg (1058lbs)/250kg (551lbs) among the same class in the industry and max. Platform occupants up to 3 persons make it ideal choice to get job done easily



Standard Features		
Active oscillating function	7-in display screen	4WD x 2WS
Proportional control with 3 joysticks	Automotive-grade sleeves for all pipes	Weighing system
Hydraulic platform leveling	Max tilt rating to 5°	Emergency stop system
Tilt protection system	Horn & buzzer	Emergency lowering system
Flashing beacon	2.44m(8') platform	Fault diagnosis system
Footswitch	Secondary guarding device	Foam-filled tires
Manual storage box	AC power to platform	Telematics-ready connector
Options & Accessories		
Foam-filled non-marking tires	Solid tires	1.45m (4'9") platform
1.83m(6') work platform	1.83m(6') /2.44m(8') platform with swinging gate	Platform work light
Glazier kit(for platform with swinging gate)	Half mesh (for platform with swinging gate)	
Overhead anti-collision device		

SINOBOOM™

PARTNERS IN ACCESS™

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

